



GDO-8 Shed Master®

550N WEATHER RESISTANT ROLL UP GARAGE DOOR OPENER

Perfect for exposed applications like perimeter doors and open carports, the weather-resistant **GDO-8 Shed Master®** is designed for the harsh Australian climate. Along with its IP24 rating, it has:

Safety



soft stop/start



intelligent safety system (iss)



door profiling

Drive & Mounting Systems



dc motor



slimfit

Operating Modes & Features



service indicator



weather resistant



lockout system

Optional Extras



solar



courtesy light



from gate to garage

Technical Specifications		GDO-9 Enduro™	GDO-9 Dynamo™	GDO-11 Ero™	GDO-6 EasyRoller®	GDO-8 Shed Master®
Input/Motor Voltage		230Vac - 240Vac 50Hz / 24Vdc				
Transformer Rating		150VA	100VA	72VA	100VA	72VA
Standby power		2.2W	2.2W	2.2W	2.2W	2.8W
C-Rail Options	1-piece Aluminium C-Rail with Belt	Standard	N/A	N/A	N/A	
	1-piece Aluminium C-Rail with Chain	Optional	N/A	N/A		
	1- or 4-piece Steel C-Rail with Chain	N/A	Standard	Standard		
	1- or 4-piece Steel C-Rail with Belt	N/A	Optional	Optional		
Min. Headroom <i>(top of C-Rail to highest point of door travel)</i>		72mm	57mm	57mm	N/A	N/A
Min./Rec. Sideroom <i>(curtain edge to inside of door bracket)</i>		N/A	N/A	N/A	40mm/80mm	40mm/80mm
Weather-Resistant Rating		IP20	IP20	IP20	IP20	IP24
Maximum Door Area		18.0m ²	16.5m ²	13.5m ²	16.5m ²	13.5m ²
Peak Lifting Force		1,000N	800N	650N	600N	550N
Typical Travel Speed		110mm/sec	130mm/sec	140mm/sec	120mm/sec	100mm/sec
Receiver storage capacity		14 x 4 button Transmitters	14 x 4 button Transmitters	8 x 4 button Transmitters	14 x 4 button Transmitters	8 x 4 button Transmitters
Receiver/Transmitter type		Multi-frequency UHF FM (434.37, 433.47 & 433.92MHz)				
Coding type		Code hopping (Non-linear encryption algorithm)				
No. of code combinations		4.29+ billion random codes				
Warranty		2 year / 5,000 cycle parts warranty				

Optional Accessories & Outputs

Battery Backup	✓	✓	✓	✓	✗
SmartSolar™	✓	✓	✓	✓	✓
Auxiliary Output	✓	✓	✓	✓	✓

